



# TOUR LSV™

## FACE NEW ROADS.

Transporting passengers just got easier with the all-new street legal Cushman® Tour LSV, offered exclusively with an ELiTE® Lithium drivetrain powered by Samsung SDI technology. The backup camera, side and rearview mirrors, lap belts and additional safety features provide riders with the security and comfort of being certified to the highest LSV standard. Go further in comfort, style, and accessibility with the Tour LSV.

**ELiTE**<sup>®</sup>  
LITHIUM

**STREET LEGAL**  
FMVSS 500 & SAE  
J2358 CERTIFIED

**FOUR  
FORWARD-FACING  
SEATS**

**25 MPH**  
MAX SPEED

**ZERO  
MAINTENANCE**  
ELiTE LITHIUM BATTERY



# TOUR LSV / ELiTE

## STREET LEGAL

### ELiTE LITHIUM POWERTRAIN

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- 6.2 Triple Pack Battery Option for Extended Range

### STANDARD FEATURES

- Backup Camera
- Rear View Mirror with Integrated Display
- Pedestrian Warning System
- Maximum Speed of 25 MPH
- Lap Belts
- 4 Wheel Hydraulic Brakes
- Center High Mount Brake Light
- Large Fender Flares
- OPS (Operator Protective Structure) Rated Canopy Structure
- Side View Mirrors
- Turn Signals and Horn
- Stylish Dash with Versatile Storage Areas
- LED Headlights
- Brake Lights
- Limited Slip Differential
- Automatic Park Brake
- VIN number

### OPTIONS & ACCESSORIES

- IntelliGauge™ (ELiTE Only)
- USB Ports
- Premium Steering Wheel
- Brush Guard
- Lighted License Plate Kit
- Lockable Trunk
- Cargo Basket
- Reflective Safety Triangle
- Enclosure

**CUSHMAN.COM**

### BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat
FRONT BODY AND FINISH	Injection Molded TPO
REAR BODY AND FINISH	Thermoform ABS
OPTIONAL BODY COLORS	Black, Bright White, Flame Red, Metallic Charcoal, Ocean Grey, Patriot Blue, Slate
STANDARD SEAT COLORS	Black, Grey, Stone Beige
PREMIUM SEAT COLORS	Black, Mushroom, Grey

### DIMENSIONS

OVERALL LENGTH	106.5 in (271 cm)
OVERALL WIDTH	46 in (117 cm)
OVERALL HEIGHT W/ CANOPY	75.5 in (192 cm)
WHEEL BASE	77.5 in (197 cm)
FRONT WHEEL TRACK	38 in (97 cm)
REAR WHEEL TRACK	39 in (99 cm)
GROUND CLEARANCE @ DIFFERENTIAL	7 in (18 cm)

### POWER

POWER SOURCE	56.7V DC
MOTOR TYPE	AC Induction
HORSEPOWER (KW)	11.7 hp (8.7 kW)
ELECTRICAL SYSTEM	56.7V
BATTERIES (TYPE)	Twin Pack
KEY OR PEDAL START	Pedal
BATTERY CHARGER	World Charger
SPEED CONTROLLER	235 Amp AC Controller
DRIVETRAIN	Motor Shaft Direct Drive
TRANSAXLE	Limited Slip Differential with Helical Gears
GEAR SELECTION	Dash Mounted FNR/Key Switch
REAR AXLE RATIO	16.99:1 (Forward)

### PERFORMANCE

SEATING CAPACITY	4-Person
DRY WEIGHT	966 lb (437 kg)
CURB WEIGHT	1040 lb (471 kg)
DASH / IP STORAGE CAPACITY	1123 sq in (18403 sq cm)
VEHICLE LOAD CAPACITY	800 lb (363 kg)
TURNING RADIUS	12.85 ft (3.92 m)
OUTSIDE CLEARANCE CIRCLE	23.9 ft (7.3 m)
SPEED (LEVEL GROUND)	25 mph (40.2 kph)
TOWING CAPACITY	500 lb (227 kg)

### STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion
SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers
BRAKES	Four-Wheel Hydraulic, Front Disk; Rear Self-Adjusting Drum
PARKING BRAKE	Automatic Electromagnetic
TIRES	Kenda K500 20 x 8-10" (6-ply Tires)